## BCT600IG

## 60 cm Induction 4 Zone Cooktop including Indyflex™ Zone





|                                 |                              | Cooktop Type                 | Width |                                   | Burner<br>Configuration | Display Type          |
|---------------------------------|------------------------------|------------------------------|-------|-----------------------------------|-------------------------|-----------------------|
|                                 |                              | Induction                    | 60 cm |                                   | 4 Zone                  | Semi Direct<br>Access |
| Main Features                   |                              | Dimensions & Weights         |       |                                   |                         |                       |
| Cooking Zones:                  | 4 x Induction with Flexizone | Built-in dimensions (W x D): |       | 560 mm x 490 mm                   |                         |                       |
| Control Type:                   | Semi Direct Access Touch     | Unpacked height:             |       | 52 mm                             |                         |                       |
| Construction Type:              | Frameless Glass              | Unpacked width:              |       | 590 mm                            |                         |                       |
| Cooking Levels:                 | 9 per Zone                   | Unpacked depth:              |       | 520 cm                            |                         |                       |
| Indyflex™ Zone:                 | Yes                          | Unpackaged Weight:           |       | 9.5 Kg                            |                         |                       |
| Automatic Pan Detection         | Yes                          | Packaged Height:             |       | 125 mm                            |                         |                       |
| Total Electric Power:           | 7.2 kW                       | Packaged Width:              |       | 650 mm                            |                         |                       |
| Fuse:                           | min. 16 A x 2                | Packaged Depth:              |       | 600 mm                            |                         |                       |
| Control Features                |                              | Packaged Weight:             |       | 10.5 Kg                           |                         |                       |
| Separate Controls for Each Zone | Yes                          | For more detailed dimensions |       | See page 2                        |                         |                       |
| Booster Function:               | Yes                          |                              |       |                                   |                         |                       |
| Timer :                         | Yes                          | Sku:                         |       | 7757189261                        |                         |                       |
| Stop & Go Function:             | Yes                          | Ean Code:                    |       | 8690842598845                     |                         |                       |
| On-Off Indicator Light:         | Yes                          | Manufacturers Warranty:      |       | 2 Years + 3 Years by Registration |                         |                       |
| Key Lock/Cleaning Lock:         | Yes                          | Launch Date:                 |       | October 2023                      |                         |                       |
| Safety                          |                              |                              |       |                                   |                         |                       |
| Overflow Safety Switch Off:     | Yes                          |                              |       |                                   |                         |                       |
| Overheat Safety System:         | Yes                          |                              |       |                                   |                         |                       |
| Automatic Switch Off:           | Yes                          |                              |       |                                   |                         |                       |
| Cooking Zones                   |                              |                              |       |                                   |                         |                       |
| Rear Left Zone:                 | 2.0/2.3 kW (Ø 180 mm)        |                              |       |                                   |                         |                       |
| Rear Right Zone:                | 2.0/2.3 kW (Ø 210 mm)        |                              |       |                                   |                         |                       |
| Front Left Zone:                | 2.0/2.3 kW (Ø 180 mm)        |                              |       |                                   |                         |                       |
| Front Right Zone:               | 1.6/1.8 kW (Ø 145 mm)        |                              |       |                                   |                         |                       |





**Semi Direct Access Control** - Giving you control and flexibility in the kitchen, touch controls for each cooking zone allow you to adjust the heat level of your pots and pans separately, at the simple touch of a button.



IndyFlex<sup>™</sup> Zone - Merge two zones together at the touch of a button. Great for when you need to use a larger pan, you can easily merge two cooking zones together thanks to IndyFlex<sup>™</sup> technology in our induction cooktop.



**Booster Function** - Helping you save time, use the booster function to set the cooking zone to its maximum power, reaching the highest temperature quickly and efficiently.





