

Dimensions:220*110mm



技术要求

- 1,标贴背面涂不干胶,并贴保护纸,粘接牢固,不卷边;
- 2,字迹清晰,用溶剂及酒精擦拭,15秒后不被擦去;
- 3,颜色,字体,字样,位置等按本图制作;
- 4,工作温度<100° C
- 5,外框不需要印刷
- 6,颜色标准CMYK,C表示青色, M表示红, Y表示黄, K表示黑
- 7,尺寸: 220*110
- 8,放在说明书包装袋中。

TECHNICAL REQUIREMENT

- 1、 Back of energy label past adhesive glue,and protective paper,carefully pasted and no warping.
- 2、 The words should be clear,we use alcohol and solvent to erase the words for 15s, and the words should still remains.
- 3、 Color of font ,the type of words should be made according to this drawings.
- 4、 Temperature<100 °C
- 5、 Frame don't print
- 6、 color standard CMYK,C-cyan,M-red,Y-yellow, K-black
- 7、 dimensions: 220*110
- 8、 In the IB polybag.

借(通)用件登记

描图

描校

底图总号

签字

日期

				beko		Material 铜版纸 Art paper						
				DATE		NAME		节能标贴 energy label				
				the tolerances standard:								PART NO.
								Mat. Class	Mat. Order No.	Type	Srd. Change	1/1
								23	0321	09	93	PAGE NO. 1
								Substitute for - - - - -				TOTAL 1
Type	AA	2019.03.06	amy fan	Prepared N	Approved N							