226600030 ΑD

7732187919239999990801



23 999999 08

7732187919239999990801



PRDF34550SS Class I

3,7 kW 220-240 V ~ ;60 Hz 2AC~N 7732187919 23 999999 08





Conforms to UL Std. 858 Cert. to CSA Std. CSA -E60335-2-6



PRDF34550SS

Class I 3,7 kW 220-240 V ~ :60 Hz 2AC~N 7732187919 23 999999 08



4004180



Conforms to UL Std. 858 Cert. to CSA Std. CSA -E60335-2-6



Manufactured by Arcelik A.S. Cooking Appliances Plant - Bolu Yukarı Soku Mahallesi Arçelik Sokak No:1/14300 **BOLU MERKEZ / BOLU. TURKEY**

The gas appliance pressure regulator must be set for the gas with which the appliance is used. "The Installation drawing are described in instruction manual"

226600030

ΔD 7732187919239999990801




Total Rate: Nat 62000 BTU/h- LP 50750 BTU/h

PRDF34550SS

23 999999 08

7732187919239999990801



23 999999 08

beko

PRDF34550SS

Nat - I P

220-240 V ~ :60 Hz 2AC~N

7732187919 23 999999 08

Conforms to ANSI Z21.1-2018 - Household Cooking Appl Certified to CSA 1.1-2018 - Household Cooking Appl Certified to CSA 2.17-2017 - Gas-fired appliances for use at high altitudes

Manifold Pressure Natural gas 5 inches WC

Manifold Pressure LP gas 10 inches WC

4004180

BTU/h

Rear left: Nat 4000/LP 3000

Front left: Nat 20000/LP 16500

Rear right: Nat 8000/LP 6500 Front right: Nat 20000/LP 16500

Center: Nat 10000/LP 8250

This appliance can be used with LP gas and Nat. gas. It is shipped from the factory adjusted for use with Nat. gas. Conversion orifices are located as described in the user manual. Follow the instructions packaged with the orifices for gas conversion.

RDF34550SS