
Manufactured by Arcelik A.S. Cooking Appliances Plant - Bolu Yukarı Soku Mahallesi Arçelik Sokak No:1 /14300 BOLU MERKEZ / BOLU, TURKEY

The gas appliance pressure regulator must be set for the gas with which the appliance is used. "The Installation drawing are described in instruction manual"

226600103 AB

7732188004239999990801



23 999999 08

7732188004239999990801



PRGR34552SS 23 999999 08

beko

PRGR34552SS

PRGR34552SS

Nat - LP 120 V~:60 Hz

4 4 A

Conforms to ANSI Z21.1-2018/Household Cooking Appl Certified to CSA 1.1 -2018/Household Cooking Appl Certified to CSA 2.17-2017-Gas-fired appliances for use at high altitudes

Manifold Pressure Natural gas 5 inches WC
Manifold Pressure LP gas 10 inches WC

wc .

Intertek 4004180

Total Rate: Nat 84500 BTU/h- LP 71250 BTU/h

7732188004 23 999999 08

Front left: Nat 20000/LP 16500

BTU/h
Rear left: Nat 8000/LP 6500

Rear right: Nat 8000/LP 6500 Front right: Nat 20000/LP 16500 Oven: Nat 18500/LP 17000 Broil: Nat 13000/LP 11000

This appliance equiped only for altitudes:0-4500 ft / 0-1370 m

Center:Nat 10000/LP 8250

This appliance can be used with LP gas and Nat. gas. It is shipped from the factory adjusted for use with Nat. gas. Conversion orifices are located as described in the user manual. Follow the instructions packaged with the orifices for gas conversion.



